

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



PATENT
3009-1008

THE U.S. PATENT AND TRADEMARK OFFICE

In re application of

David Stanley Ohn TINN

Conf. 3242

Application No. 10/014,582

Group 3679

Filed December 14, 2001

Examiner John R. COTTINGHAM

CONNECTOR DEVICE

CLAIM TO PRIORITY

Assistant Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

May 4, 2004

Sir:

Applicant(s) herewith claim(s) the benefit of the priority filing date of the following application(s) for the above-entitled U.S. application under the provisions of 35 U.S.C. § 119 and 37 C.F.R. § 1.55:

<u>Country</u>	<u>Application No.</u>	<u>Filed</u>
UNITED KINGDOM	0030490.7	December 14, 2000

Certified copy(ies) of the above-noted application(s) is(are) attached hereto.

Respectfully submitted,

YOUNG & THOMPSON

Benoît Castel
Benoît Castel, Reg. No. 35,041
745 South 23rd Street
Arlington, VA 22202
Telephone (703) 521-2297
Telefax (703) 685-0573
(703) 979-4709

BC/psf

Attachment(s): 1 Certified Copy(ies)





INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was subsequently filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Andrew

Dated 19 April 2004



Patents Form 1/77

Patents Act 1977
(Rule 16)



14DEC00 ES91507-1 C03029
P01/7700-0.00-0030490.7


14 DEC 2000

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ



1. Your reference

KKL16 - GB

2. Patent application number

(The Patent Office will fill in this part)

0030490.7

3. Full name, address and postcode of the or of each applicant (underline all surnames)

KEE KLAMP LIMITED

10 WORTON DRIVE

WORTON GRANGE

READING RG2 0TQ

GB

7043615001

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

4. Title of the invention

CONNECTOR DEVICE

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

J. R. BADGER

6 SIMPSON ROAD

WYLDE GREEN

SUTTON COLDFIELD

WEST MIDLANDS

B72 1EP

Patents ADP number (if you know it)

949362001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

9

Claim(s)

4

Abstract

-

Drawing(s)

2

428

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

1/1

11.

I/We request the grant of a patent on the basis of this application.

Signature

J. R. BAKER

Date

12/12/00

12. Name and daytime telephone number of person to contact in the United Kingdom

J. R. BAKER


0121 382 5143

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.



Statement of inventorship and of right to grant of a patent

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference KKL 16
2. Patent application number (if you know it) 0030490.7
3. Full name of the or of each applicant
KEE KLAMP LIMITED
4. Title of the invention
CONNECTOR DEVICE
5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent
By virtue of Section 39(1)(a)

6. How many, if any, additional Patents Forms 7/77 are attached to this form?
(see note (c))

7. I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to.

Signature

J. R. Badger

Date


14/3/02

8. Name and daytime telephone number of person to contact in the United Kingdom
J. R. BADGER 0121 382 5143

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

80630 SB 16



Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

David Stanley Ohn TINN
Nuthatch
Bigfrith Lane
Cookham Dean
Berkshire
SL6 9UQ

8347118001

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Reminder

Have you signed the form?

Patents ADP number (if you know it):

CONNECTOR DEVICE

This invention relates to a connector device for forming a structural inter-connection between two members and which permits variation of the angle of inter-connection.

The invention relates also to an assembly, and method of forming an assembly, of two members inter-connected by at least one said connector device.

One example of an application for which the present invention seeks to provide an improved connector device is that of a structure of metal tubes employed to form a handrail for stairs, steps or a ramp.

Many types of tube connectors have been proposed and used successfully for such structures. An example of one type of tube connector which is relatively low in cost is one made from malleable cast iron and having boss formations each for location of a grub screw whereby one or more tubular members may be slid into the or each housing formed by the cast tube connector and locked into position by tightening of the grub screws.

In an installation, such as for a stairway or ramp, which is required to support a hand rail in a position inclined relative to the horizontal and other members of the rail assembly, it is known to provide a connector device of a type having a through-bore to receive one of a vertical support post and inclined handrail, and a stem portion for location within a housing provided by a conventional type three-way connector fitted to the other of the vertical support post and inclined handrail.

Although use of said connector device and three-way connector is found to provide a strong, reliable and long lasting inter-connection of a vertical support post and inclined hand rail, the assembly procedure is difficult for an operator to perform single-handed. That difficulty arises because of the tendency for the stem portion of one or more of a required series of connector

devices to slip axially outwards from the housing of the three-way connector as other connector devices in the series are assembled, and prior to tightening of locking screws which in the finished assembly firmly lock together each associated pair of connector device and three-way connector.

The present invention seeks to provide an improved connector device, safety rail installation, and method of assembly of a safety rail installation whereby the aforescribed difficulty is mitigated or overcome.

In accordance with one aspect of the present invention a connector device comprises a body portion having a bore defining a housing to receive one of two members to be inter-connected and a stem portion of substantially cylindrical form having a major axis disposed substantially perpendicular to the major axis of said bore defined by the body portion, said stem portion being adapted to be received, in use, in a housing defined by a bore of a second of the two members to be inter-connected by the connector device, and said stem portion comprising in the outer surface thereof an annular groove having the major axis thereof coincident with the major axis of the stem portion and said annular groove being provided axially inwards from the distal end of the stem portion.

The stem portion may be of a hollow, tubular form. If the stem portion is hollow it is preferred that the wall thickness of the stem portion at an axial position aligned with the annular groove is substantially equal to that wall thickness of the stem portion at least at a position to one side of the groove.

The annular groove preferably is of substantially uniform width and depth as considered in a circumferential direction of the groove. It is further preferred that the width of the groove is equal to or greater than the diameter of a locking means, such as a grub screw, carried by the second of the two members to be inter-connected. The groove may comprise a rectangular or curved shape in cross-section i.e. in a cross-sectional plane containing the major axis of the stem portion. Particularly in the case of use with a member having a locking means the leading edge of which is of a conical shape, the

groove may be of 'V' shape in cross-section; the included apex angle of the 'V' shape preferably corresponds with that of the leading edge of the locking means.

An example of a particularly suitable material for the connector device of the invention is cast aluminium. Other materials such as cast iron or high strength plastics may be used.

The invention envisages that the outer surface of the stem portion of the connector device may have a diameter corresponding to the inner diameter of a cylindrical housing defined by the body portion. However these diameters may be different, particularly if the connector device is to be used to connect a handrail of a different diameter tube to that of a support post. The body portion may define a single through-bore or, for example, two housing sections which may be either axially aligned or inclined relative to one another.

At the surface of the stem portion the annular groove preferably has a width, i.e. dimension in the direction of the major axis of the stem portion, which is at least one quarter and more preferably at least one third of the axial length of the stem portion.

The ratio of the axial length of the stem portion to the diameter of the stem portion preferably lies in the range 2 to 0.5. A ratio in the range 1.5 to 0.75, e.g. a ratio of 1.0, is considered particularly suitable.

The body portion of the connector device may provide an abutment surface for contact, in use, by an end of said housing of said second of two members to be inter-connected by the connector device.

In accordance with another of its aspects the present invention provides a method of forming an assembly of inter-connected members in which one elongate member is secured to other members at a plurality of positions axially spaced along the length of the elongate member, said method

comprising providing a plurality of connector devices each of a kind in accordance with the present invention for inter-connecting a first and a second member, providing a plurality of second members each having a housing which defines a bore into which the stem portion of a respective connector device may be received and said housing of the second member comprising locking means adapted to extend into the annular groove of the connector device and to lie either in a retracted position whereby the stem portion may move freely into and out of said housing or one of at least two locking positions, a first locking position being one at which the locking means inhibits axial movement of the stem portion outwards from said housing but allows relative rotational movement of the stem portion and housing and the second locking position being one at which the locking means bears against the stem portion to inhibit both said axial and rotational movements, the method further comprising the steps of providing an elongate member to extend through a passage defined by one of the connector device and second member of each pair of connector device and second member and of moving locking means of a second member to said first position in the groove of a connector device whilst one or more other pairs of connector device and second member are positioned relative to the elongate member.

Preferably at least some and more preferably all of the locking means of the second members are moved to the second locking position when the inter-connected members of the assembly are in the required positions relative to one another.

The elongate member of the method aspect of the invention may be a first member which extends through a through-bore defined by one or more connector devices of a series. The second members may be secured for example to a wall surface or other structure or may comprise a housing, for example a through housing, which receives a support member such as a vertical post.

The elongate member of the method aspect of the invention may be a third member which extends through a through-bore defined by one or more

second members of the series. The connector devices may be secured for example to respective vertical posts which may be located in housings defined by the body portions of the connector devices.

In a series of connector devices and associated second members an elongate member may extend through the combination of at least one through housing defined by the body portion of a connector device, and at least one through housing defined by a second member.

When the method of the invention is applied to forming an assembly comprising an inclined hand rail the method may comprise use of connector devices each of a kind having a bore defined by the body portion and providing a respective vertical post to extend into each said bore, and the second of the two members to be inter-connected by the connection device may be a three-way type connector having a through-bore, with the inclined hand rail member extending through the through-bores of a plurality of said second members, the locking means of one second member being arranged in said first position to locate axially with one connector device whilst a similar inter-connection is formed between a second and subsequent associated pairs of connector devices and second members, and thereafter moving each said locking means to said second position thereby to firmly inter-connect the respective pairs of connector devices and second members.

Whilst it is envisaged that the method typically may comprise securing the connector device of the invention to a vertical post, for example by means of a grub screw in the wall of the body portion of the connector device, the connector device of the present invention may be arranged with a hand rail member extending therethrough, and vertical posts for support of the hand rail may each be connected to said connector device by means of a second member such as a three-way connector secured to the vertical post.

The present invention envisages that in the case of use of a three-way connector having a housing to receive the stem portion of a connector device, and comprising a through-bore for receiving an elongate member, preferably

the major axis of said housing is substantially perpendicular to the major axis of said through-bore.

In accordance with a further of its aspects the present invention provides an assembly of elongate members inter-connected by a connector device in accordance with the present invention, and an assembly formed by the method of the invention.

One embodiment of the present invention will now be described, by way of example only, with reference to the accompanying diagrammatic drawings in which:-

Figure 1 is a plan view of a connector device in accordance with the present invention;

Figure 2 is a side view of the connector device of Figure 1;

Figure 3 is a section on the line "X - X" of Figure 2;

Figure 4 is an end view in the direction of the arrow 1V of Figure 2;

Figure 5 is an end view in the direction of the arrow V of Figure 2, and

Figure 6 is a perspective view of part of a part formed hand rail assembly of the present invention.

With reference to Figures 1 to 5, a connector device 10 comprises a body portion 11 and a stem portion 12 integrally formed from cast aluminium.

The body portion 11 comprises a through-bore 14 dimensioned to receive a standard size vertical post of a hand rail assembly. The wall of the through-bore 14 is provided with a screw threaded aperture 15 to receive a grub screw (not shown) in known manner for the purpose of enabling a vertical post to

be secured axially within the through-bore 14 upon tightening of the grub screw.

The stem portion 12 is of a tubular form and has a major axis 16 which extends perpendicular to the major axis 17 of the body portion. The axis 16 of the stem portion is the major axis of a substantially cylindrical outer surface 18 defined by the stem portion. The stem portion is, in this embodiment, of a hollow form, and the cavity defined by the stem portion extends into communication with the through-bore 14 of the body portion. The substantially cylindrical outer surface 18 of the stem portion comprises a recess in the form of a circumferentially extending groove 19 the major axis of which is coincident with the major axis 16 of the stem portion. The groove 19 is of a curved shape in cross-section (see Figure 3) and the radial thickness of the wall of the stem portion where it defines the annular groove 19 is equal to the wall thickness at the distal end 20 and at an inner end 21 lying between the groove 19 and the body portion 11.

The body portion 11 provides an annular abutment face 22 adjacent the inner end section 21 of the stem portion. The length of the stem portion between the abutment 22 and distal end 20 is substantially equal to the diameter of the cylindrical surface 18 of the stem portion. That axial length of the stem portion is also double the axial length of the circumferentially extending annular recess 19.

In this embodiment the depth of the recess is approximately fifty percent of the wall thickness of the stem portion, that being sufficient to ensure that when the housing of a second member is fitted over the stem portion and a grub screw or like locking means carried by the second member is moved radially inwards, that locking means can restrain axial movement of the stem portion outwards from the housing of the second member whilst nevertheless permitting the stem portion to rotate relative to the second member.

Part of a hand rail assembly in a part formed condition is shown in Figure 6. This assembly comprises the connector device 10 of Figures 1 to 5 secured to

a vertical post member 31 by means of a grub screw carried in the screw aperture 15. The hand rail 32 for mounting in inclined position relative to the vertical post has secured thereto a three-way type connector 33. The connector 33 comprises a through-bore through which the rail 32 extends and which is locked in position by means of a grub screw in a screw thread 34. The three-way connector additionally comprises a housing portion 35 which extends perpendicularly relative to the through-bore and is dimensioned to be a sliding fit over the stem portion of the connector 10.

Figure 6 shows the housing of the three-way connector at the point at which it is in alignment with and about to be slid over the stem portion of the connector device 10. When fully slid into position, with the end of the housing portion 35 of the three-way connector contacting the flange 22, the screw thread 38 in the wall of the housing aligns axially with the recess 19 in the stem portion of the connector device. Accordingly tightening of a grub screw in the screw threaded aperture 38 brings the inner end of the grub screw into a mechanical interlock position in the groove.

To assist in assembly of the other components required to form a plurality of connections between a hand rail and vertical support posts the grub screw in the aperture 38 optionally may be lightly tightened so that in addition to providing axial interlock it tends to resist relative rotational movement. Subsequent to assembly of the components in their required relative positions the grub screws 38 of the respective three-way connectors of a series may all be more firmly tightened, as well as those locking the hand rail to the through-bore of each three-way connector.

The grub screw in each screw thread 38 or resisting relative rotation of the three-way connector and connector device is required only to prevent relative rotational movement during the assembly operation, and that resistance to rotation is not required in the final assembly when other connectors are in position. Accordingly those grub screws do not need to be tightened with such great force and in consequence the wall strength of the stem portion of the connector device does not need to be as great as would otherwise would

be necessary. A saving in weight and material cost for the stem portion is thereby achieved in addition to effectively resisting axial separation of associated pairs of connector devices and three-way connectors during the assembly operation.

KKL16

CLAIMS

1. A connector device comprising a body portion having a bore defining a housing to receive one of two members to be inter-connected and a stem portion of substantially cylindrical form having a major axis disposed substantially perpendicular to the major axis of said bore defined by the body portion, said stem portion being adapted to be received, in use, in a housing defined by a bore of a second of the two members to be inter-connected by the connector device, and said stem portion comprising in the outer surface thereof an annular groove having the major axis thereof coincident with the major axis of the stem portion and said annular groove being provided axially inwards from the distal end of the stem portion.
2. A connector device according to claim 1, wherein the stem portion is of a hollow tubular form.
3. A connector device according to claim 2, wherein the wall thickness of the stem portion at an axial position aligned with the annular groove is substantially equal to that wall thickness of the stem portion at least at a position to one side of the groove.
4. A connector device according to any one of the preceding claims, wherein the annular groove is of substantially uniform width and depth as considered in a circumferential direction of the groove.
5. A connector device according to any one of the preceding claims, wherein the groove is of a curved shape in cross-section.
6. A connector device according to any one of the preceding claims, wherein the ratio of the axial length of the stem portion to the diameter of the stem portion lies in the range 2 to 0.5.
7. A connector device according to claim 6, wherein the said ratio is in the range 1.5 to 0.75.

8. A connector device according to claim 7, wherein said ratio is substantially equal to 1.0.
9. A connector device according to any one of the preceding claims, wherein the body portion provides an abutment surface at one end of the stem portion for contact, in use, by an end of a housing of said second of the two members to be inter-connected by the connector device.
10. A connector device according to any one of the preceding claims, wherein the body portion defines a single through-bore to receive one of two members to be inter-connected.
11. A connector device according to any one of the preceding claims, wherein the annular groove at the surface of the stem portion has a width which is at least one quarter of the axial length of the stem portion.
12. A connector device according to claim 11, wherein the width of the annular groove is at least one third of the axial length of the stem portion.
13. A connector device according to any one of the preceding claims, wherein the stem portion and body portion are integrally formed from cast or moulded material.
14. A connector device according to claim 1 and substantially as hereinbefore described.
15. An assembly of elongate members wherein one of said elongate members has secured thereto a connector device according to any one of the preceding claims and the other elongate member has secured thereto a connector comprising a housing into which the stem portion of the connector device is received, said housing comprising locking means in engagement with the annular groove of the stem portion thereby to resist

axial separation of the stem portion of the connector device and said housing which receives said stem portion.

16. An assembly according to claim 15 and substantially as hereinbefore described.
17. A method for forming an assembly of inter-connected members in which one elongate member is secured to other members at a plurality of positions axially spaced along the length of the elongate member, said method comprising providing a plurality of connector devices each of a kind in accordance with the present invention for inter-connecting a first and a second member, providing a plurality of second members each having a housing which defines a bore into which the stem portion of a respective connector device may be received and said housing of the second member comprising locking means adapted to extend into the annular groove of the connector device and to lie either in a retracted position whereby the stem portion may move freely into and out of said housing or one of at least two locking positions, a first locking position being one at which the locking means inhibits axial movement of the stem portion outwards from said housing but allows relative rotational movement of the stem portion and housing and the second locking position being one at which the locking means bears against the stem portion to inhibit both said axial and rotational movements, the method further comprising the steps of providing an elongate member to extend through a passage defined by one of the connector device and second member of each pair of connector device and second member and of moving locking means of a second member to said first position in the groove of a connector device whilst one or more other pairs of connector device and second member are positioned relative to the elongate member.
18. A method according to claim 17, wherein at least some of the locking members are moved to the second locking position when the inter-

connected members of the assembly are in the required positions relative to one another.

19. A method according to claim 17, or claim 18, wherein said elongate member is provided as a first member which extends through a through-bore defined by at least one connector device of the series.
20. A method according to any one of claims 17 to 19, wherein said elongate member is provided as a third member which extends through a through-bore defined by at least one connector device of the series.
21. A method of forming an assembly comprising an inclined hand rail, said method comprising use of connector devices each of a kind having a bore defined by the body portion and providing a respective vertical post to extend into each said bore, and the second of the two members to be inter-connected by the connection device being a three-way type connector having a through-bore, with the inclined hand rail member extending through the through-bores of a plurality of said second members, the locking means of one second member being arranged in said first position to locate axially with one connector device whilst a similar inter-connection is formed between a second and subsequent associated pairs of connector devices and second members, and thereafter moving each said locking means to said second position thereby to firmly inter-connect the respective pairs of connector devices and second members.
22. A method according to claim 17 or claim 21 and substantially as hereinbefore described.
23. An assembly formed by a method according to any one of claims 17 to 22.








FIG. 5

2 / 2




FIG. 6

Document Filed By:

Young & Thompson

745 South 23rd Street

Arlington, Virginia 22202

Telephone 703/521-2297

SN 10/014, 582 Filed Dec. 14, 2001